





- B. It adheres very well to synthetic floors such as PVC tiles.
- C. The tape will also adhere to concrete floors and can be expected to remain intact for several months depending on traffic.
- D. The tape is yellow and printed in black with the ESD logo as per EN 61340-5-1 and the text 'ESD Protected Area'.
- E. The carrier tape is laminated with a clear film to protect the print. The tape is not antistatic as it is intended for use outside the EPA.
- F. The tape is a highly visible identification of the boundaries of an EPA.
- G. Available in two designs.

	_
EN 61340-5-1 paragraph 4.3 Signs for ESD protected	
areas (EPA) ESD sensitivity symbol "Sign(s)shall be	
clearly visible to personnel before they enter the EPA	
and, where applicable, from inside the EPA. Where	
applicable, signs shall mark the EPA boundary."	
Paragraph 4.4 Marking of EPA bonding points (EBP) "All	
EBP shall be marked or labelled." Per EN 61340-5-2	
paragraph 5.1.1 "The boundaries of the EPA need	
defining and will vary between different types of EPA.	

but will typically have coloured (but not electrostatic

generative) markings on the floor."

Item	Description
210300	Floor Marking Tape, 75mm wide, 33m long
210310	Floor Marking Tape with Arrows, 50mm wide, 66m long

Width tolerance ±5 mm



Specifications and procedures subject to change without notice.



## Floor Marking Tape

VERMASON

UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH, HERTS, SG6 2TD UK

PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440 E-MAIL: <u>Service@Vermason.co.uk</u>, INTERNET: <u>Vermason.co.uk</u> Drawing Number 210300

June 2010