

Item	Description
<u>241060</u>	Rigid Conductive Box, 35mm x 35mm x 11mm, Empty
<u>241065</u>	Rigid Conductive Box, 35mm x 35mm x 11mm, 6mm HD in Base Only
<u>241045</u>	Rigid Conductive Box, 75mm x 51mm x 14mm, Empty
<u>241050</u>	Rigid Conductive Box, 75mm x 51mm x 14mm, 6mm HD in Base, FX in Lid
<u>241030</u>	Rigid Conductive Box, 90mm x 64mm x 16mm, 6mm HD in Base, FX in Lid
<u>241015</u>	Rigid Conductive Box, 108mm x 83mm x 13mm, 6mm HD in Base, FX in Lid
<u>241005</u>	Rigid Conductive Box, 230mm x 128mm x 20mm, 6mm HD in Base, FX in Lid
<u>241085</u>	Rigid Conductive Box, 230mm x 128mm x 30mm, Empty
<u>241090</u>	Rigid Conductive Box, 230mm x 128mm x 30mm, 6mm HD in Base Only
<u>241095</u>	Rigid Conductive Box, 230mm x 128mm x 40mm, Empty
<u>241100</u>	Rigid Conductive Box, 230mm x 128mm x 40mm, 6mm HD in Base, FX in Lid

All dimensions are internal

"ESD protective packaging.... when required, shall be defined for all material movement within protected areas, between protected areas, between job sites, field service operations and to the customer."

Per Table 4, conductive packaging required range 1 x 10² to less than 1 x 10⁵ ohms tested per IEC 61340-2-3. [EN 61340-5-1 Edition 1.0 clause 5.3.4 Packaging and Table 4]



Description:

Vermason Rigid Conductive Boxes are marked with the ESD protective symbol. Boxes can be supplied with or without high density foam for insertion of component leads or low density foam which acts as a cushioning material. Meets EN 61340-5-1 and Packaging standard IEC 61340-5-3.

Properties:

Material:	Black conductive polypropylene
Resistance (Rs):	1×10^2 to < 1 x 10 ⁵ ohms per IEC 61340-2-3
Size Tolerance:	± 0.8mm
Melting Temperature:	80°C to 90°C
Hinge:	Moulded one-piece (241015-241065) Pin two-piece (241000-241005 and 241085-241100)
Closure:	Snap
Top Foam: Bottom Foam:	6mm thick low density foam (FX) 6mm thick high density foam (HD)

All boxes have the ESD Protective Symbol moulded into them.



Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice.

Rigid Conductive Boxes

VERMASON UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH.HERTS. SG6 2TD UK PHONE: +44 (0) 1462-672005 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number 241000

DATE: February 2014

United Kingdom