



- A. Underwriters Laboratory Listing 90P1C.
- B. Compatible with [Desco Europe Dual-Wire Continuous Monitors](#) and other brands that accept a 3.5mm phono plug.
- C. Thermoplastic elastomer strain relief molded on.
- D. Relaxed retraction coiled cord reduces tug on wearer's wrist. Black PVC insulation. Break load average 13.6 kilograms (30 pounds).
- E. Dual T-3067 tinsel conductor. Consists of stranded polyester wrapped in copper. Equivalent to 29 gauge (cir mil and/or ohms).
- F. 1 megohm ($\pm 5\%$) current limiting resistors on both conductors.
- G. Unique dual contact design is to be paired with a [Desco Europe MagSnap 360™ Wristband](#) (not included) for a superior electrical connection. The magnetic connection made with the coiled cord meets the 1-5 pound perpendicular breakaway force requirement per ANSI/ESD S1.1 to prevent accidental disconnects while allowing the worker to untether when needed. Spring loaded center contact rated to 1 million cycles.
- H. Date coded with date of manufacture in compliance with ANSI/ESD S1.1.
- I. "MagSnap 360" logo molded in compliance with ANSI/ESD S1.1.

Meets required limits of EN 61340-5-1 and requirements of ANSI/ESD S1.1.

Item	Retracted Length		Extended Length	
	X	Y	Nominal	Max
60685	305mm (12")	508mm (20")	183cm (6')	259cm (8.5')
60686	610mm (24")	813mm (32")	366cm (12')	518cm (17')
60687	762mm (30")	965mm (38")	457cm (15')	671cm (22')

U.S. Patent Pending

Unless otherwise noted, tolerance $\pm 10\%$.
Specifications and procedures subject to change without notice.



Made in the
United States of America

MagSnap 360™ Dual-Wire Coiled Cord

DESCO EUROPE
2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
HERTFORDSHIRE, SG6 1BE, UK
PHONE: +44 (0) 1462 672005
E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
60685.E

DATE:
January
2018

DESCO EUROPE