



| | Circumference | |
|-----------|---------------|-------------|
| Band Size | Min. | Max. |
| Small | 140mm (5.5") | 229mm (9") |
| Medium | 152mm (6") | 279mm (11") |
| Large | 178mm (7") | 305mm (12") |

| Item | Band Size | Coiled Cord |
|--------------|-----------|------------------------------|
| <u>60692</u> | Medium | Not Included |
| <u>60694</u> | Small | 183cm (6') (<u>60685</u>) |
| <u>60695</u> | Medium | 183cm (6') (<u>60685</u>) |
| <u>60696</u> | Large | 183cm (6') (<u>60685</u>) |
| <u>60699</u> | Large | 366cm (12') (<u>60686</u>) |

U.S. Patent Pending

- A. 0.051mm polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a Desco Europe MagSnap™ 360 Coiled Cord (not included on some items) for a superior electrical connection. The magnetic connection made with the coiled cord meets the 1-5 pound perpendicular breakaway force requirement per ANSI/ESD S1.1 to prevent accidental disconnects while allowing the worker to untether when needed.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 16mm.
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of EN 61340-5-1 and requirements of ANSI/ESD S1.1.



Unless otherwise noted, tolerance ±10%.

Specifications and procedures subject to change without notice.

MagSnap 360™ Dual-Wire Metal Expansion Wristband

DESCO EUROPE

DESCO EUROPE 2A DUNHAMS LANE, LETCHWORTH GARDEN CITY, HERTFORDSHIRE, SG6 1BE, UK PHONE: +44 (0) 1462 672005

PHONE: +44 (0) 1462 672005
E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number 60691.E

DATE: January 2018