



Blue

Grounding & Cleaning

If the material is used on top of an already properly grounded surface, [grounding hardware](#) may not be necessary. Where no properly grounded surface is available, [grounding hardware](#) is required to provide a path-to-ground. Rg compliance verification measurements must be made per EN 61340-5-1 periodically with a [surface resistance meter](#).

See Tech Bulletin [TB-7000](#) for Reztore® Surface & Mat Cleaner Application Instructions.

Limited Lifetime Warranty:

Desco Europe warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by [Desco Europe Limited Warranty](#).

RoHS 3, REACH, and Conflict Minerals Statement

See the Desco Europe RoHS 3, REACH, and Conflict Minerals Statement:

DescoEurope.com/ROHS.aspx

See the Desco Europe Limited Warranty:

DescoEurope.com/Limited-Warranty.aspx

See the Desco Europe Disclaimer:

DescoEurope.com/Disclaimer.aspx

Specifications

Standard Document

EN 61340-5-1

Meets Requirements of:

Working Surface

Electrical Properties

Property	Test Method	Value
Colour Dissipative Side		
Rp-p Resistance:	IEC 61340-2-3	1 x 10 ⁶ to < 1 x 10 ⁹ ohms
Rg Resistance:	IEC 61340-2-3	1 x 10 ⁶ to < 1 x 10 ⁹ ohms
Black Side		
Rp-p Resistance:	IEC 61340-2-3	<1 x 10 ⁶ ohms

More conductive bottom layer makes suitable for use with continuous monitors.

Physical Properties

Construction: Dual-layer Rubber
Thickness: 2mm
Texture:* Slight Emboss
Colours:* Blue

Tolerances

Width ± 6mm
Length ± 21mm for every linear metre of material
Thickness ± 10%

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

*Colour, texture, and gauge may vary between lots and mills

For product listings, please click [Here](#).



Made in the United States of America

Specifications and procedures subject to change without notice.

Statfree UC2™ DISSIPATIVE DUAL LAYER ULTRA CLEAN RUBBER

DESCO EUROPE

DESCO EUROPE
2A DUNHAMS LANE, LETCHWORTH GARDEN CITY,
HERTFORDSHIRE, SG6 1BE, UK
PHONE: +44 (0) 1462 672005
E-MAIL: Service@DescoEurope.com, INTERNET: DescoEurope.com

Drawing Number
PME-UC2

DATE:
September
2017